



# elkuch<sup>®</sup> FLEXIBLE BENT TUBING SYSTEM

## TECHNICAL SPECIFICATION (DIN)


### Bent tubing 90° single-sided with sleeve and sealing

	Ø Dimension	Length	Rm	x	y
	50	720 - 860	500	85	85
	63	905 - 1040	630	105	115
	75	1085 - 1245	750	125	115
	90	1300 - 1450	900	125	135
	110	1470 - 1710	1100	165	155
	125	1915 - 2105	1250	170	160
	140	2050 - 2340	1400	210	165
	160	2260 - 2500	1600	230	145


### Bent tubing 90° with smooth endings

	Ø Dimension	Length	Rm	x	y
	50	730 - 870	500	85	95
	63	905 - 1040	630	105	115
	75	1075 - 1255	750	125	125
	90	1280 - 1430	900	125	115
	110	1470 - 1710	1100	165	155
	125	1935 - 2125	1250	170	180
	140	2090 - 2380	1400	210	205
	160	2330 - 2570	1600	230	215

### Bent tubing 45° single-sided with sleeve and sealing

	Ø Dimension	Length	Rm	x	y
	50	445 - 520	500	85	85
	63	565 - 635	630	105	115
	75	665 - 750	750	125	115
	90	800 - 870	900	125	135
	110	910 - 1030	1100	165	155
	125	1150 - 1190	1250	170	160
	140	1220 - 1360	1400	210	165
	160	1220 - 1430	1600	230	145

### Bent tubing 45° with smooth endings

	Ø Dimension	Length	Rm	x	y
	50	455 - 530	500	85	95
	63	565 - 635	620	105	115
	75	675 - 760	750	125	125
	90	780 - 850	900	125	115
	110	910 - 1030	1100	165	155
	125	1170 - 1210	1250	170	180
	140	1260 - 1400	1400	210	205
	160	1290 - 1500	1600	230	215

All dimensions in mm. Lengths may vary slightly due to the telescopic characteristics of the bends.